

## Z-Perform™ 1000T 190 Tag



Available  
from stock  
on ZipShip

<b>Media Type</b>	Label		<b>Adhesive Type</b>	Permanent	
	Receipt			Removable	
	Tag	✓		No Adhesive	✓
	Wristband			<b>Environment</b>	Indoor
<b>Material Type</b>	Paper	✓	Outdoor		
	Synthetic		<b>Properties</b>	Cold Temperature	✓
<b>Printing Technology</b>	Direct Thermal (no Ribbon Required)			Deep Freeze	✓
	Thermal Transfer (Ribbon Required)	✓		High Temperature	
<b>Finish</b>	Matte	✓		Ultra High Temperature	
	Gloss			High Tack	
				Chemical Resistance	-

### Additional Features

- Good print quality when printed with Zebra 2300, 2100, 3400 and 3200 ribbons with a recommended Zebra printer
- BfR Recommendation XXXIV for direct contact with dry, moist and non-fatty foodstuffs
- Complies with DIN EN 71 part 3 and part 9 as the product does not release any heavy metals and does not contain prohibited amines or colourants
- BPA free

### Suggested Applications

- Indoor cold temperature labelling
- Visitor identification tags
- Admission tickets
- Warehouse and inventory control tags
- Shop floor / work in progress tracking tickets
- Shelf-edge tags
- Packaging inserts
- Pallet tagging

## Technical Specifications

	Description	Caliper
Facestock	190gsm matte white uncoated paper	170 microns
	Total	170 microns ±10%

**Recommended Zebra Printers:** Desktop, mid-range and high-performance thermal printers

**Recommended Zebra Ribbons:** 2300, 2100, 3400, 3200

**Minimum Application Temperature:** 0°C  
When the label is applied, the environment and surface should be above this temperature

**Service Temperature Range:** -43°C to 93°C  
Following correct application and appropriate dwell time (usually 24hrs) the media will withstand this temperature range

**Recommended Storage Conditions:** 1 year duration when stored at 0°C to 21°C at 35% to 50% RH  
Storage of product before use

**Expected Life Span in Application:** Indoor use, for 1 year+  
Following correct application and appropriate dwell time (usually 24hrs) we expect, but do not warrant, a life span as indicated

## Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material, please order from the ZipShip price list or order sample roll SAMPLE5284.